



Health	2
Fire	3
Reactivity	0
Personal Protection	G

Material Safety Data Sheet Ethyl acetate MSDS

Section 1: Chemical Product and Company Identification

Product Name: Ethyl acetate Catalog Codes: SLE2452, SLE2317

CAS#: 141-78-6

RTECS: AH5425000

TSCA: TSCA 8(b) inventory: Ethyl acetate

Cl#: Not available.

Synonym: Acetic Acid, Ethyl Ester Acetic Ether

Chemical Name: Ethyl Acetate

Chemical Formula: C4-H8-O2

Contact Information:

Sciencelab.com, Inc. 14025 Smith Rd. Houston, Texas 77396

US Sales: **1-800-901-7247** International Sales: **1-281-441-4400**

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call: 1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

Section 2: Composition and Information on Ingredients		
Composition:		
Nainame	CAS #	

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention.

Skin Contact:

Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops. Cold water may be used.

Serious Skin Contact: Not available.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms appear.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms appear.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: Flammable.

Auto-Ignition Temperature: 426.67°C (800°F)

Flash Points: CLOSED CUP: -4.4°C (24.1°F). (TAG) OPEN CUP: 7.2°C (45°F) (Cleveland).

Flammable Limits: LOWER: 2.2% UPPER: 9%

Products of Combustion: These products are carbon oxides (CO, CO2).

Fire Hazards in Presence of Various Substances:

Highly flammable in presence of open flames and sparks, of heat. Slightly flammable to flammable in presence of oxidizing materials, of acids, of alkalis. Non-flammable in presence of shocks.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of static discharge: Not available. Slightly explosive in presence of heat. Nonexplosive in presence of shocks.

Fire Fighting Media and Instructions:

Flammable liquid, soluble or dispersed in water. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog.

Special Remarks on Fire Hazards:

Vapor may travel considerable distance to source of ignition and flash back. When heated to decomposition it emits acrid smoke and irritating fumes.

Special Remarks on Explosion Hazards:

The liquid produces a vapor that forms explosive mixtures with air at normal temperatures. Explosive reaction with lithium tetrahydroaluminate.

Section 6: Accidental Release Measures

Small Spill:

Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.

Vapor Density: 3.04 (Air = 1)

Volatility: Not available.

Odor Threshold: 3.9 ppm

Water/Oil Dist. Coeff.: The product is more soluble in oil; log(oil/water) = 0.7

lonicity (in Water): Not available.

Dispersion Properties: See solubility in water, diethyl ether, acetone.

Solubility: Soluble in cold water, hot water, diethyl ether, acetone, alcohol, benzene.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Ingestion: May cause gastrointestinal tract irritation with nausea and vomiting. May affect blood, behavior/central nervous system (CNS depression - effects may be similar to that of inhalation). Chronic Potential Health Effects: Skin: Repeated or prolonged skin contact may cause drying and cracking of the skin. Ingestion: Prolonged or repeated ingestion may affect the liver. Inhalation: Prolonged inhalation may affect behavior/central nervous system (symptoms similar to those of acute inhalation), and cause liver, kidney, lung, and heart damage. It may also affect metabolism, and blood (anemia, leukocytosis).

Section 12: Ecological Information

Ecotoxicity:

Ecotoxicity in water (LC50): 220 mg/l 96 hours [Fish (Fathead minnow)]. 212.5 ppm 96 hours [Fish (Indian catfish)].

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14: Transport Information

DOT Classification: CLASS 3: Flammable liquid.

Identification: : Ethyl Acetate UNNA: 1173 PG: II

Special Provisions for Transport: Not available.

Section 15: Other Regulatory Information

Federal and State Regulations:

Connecticut hazardous material survey.: Ethyl acetate Illinois toxic substances disclosure to employee act: Ethyl acetate Illinois chemical safety act: Ethyl acetate New York release reporting list: Ethyl acetate Rhode Island RTK hazardous substances: Ethyl acetate Pennsylvania RTK: Ethyl acetate Florida: Ethyl acetate Minnesota: Ethyl acetate Massachusetts RTK: Ethyl acetate Massachusetts spill list: Ethyl acetate New Jersey: Ethyl acetate New Jersey spill list: Ethyl acetate